



pin	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
COM1	COM1				1A	P3	2A	P1	3A	P2	4A		kg	T2'	T2	NC	NC	NC	NC	NC
COM2		COM2			1F	1B	2F	2B	3F	3B	4F	4B	Lb	T3'	T3	NC	NC	NC	NC	NC
COM3			COM3		1G	1C	2G	2C	3G	3C	4G	4C	CM	T4'	T4	NC	NC	NC	NC	NC
COM4				COM4	1E	1D	2E	2D	3E	3D	4E	4D	P7	T5'	T5	NC	NC	NC	NC	NC

**PLEASE SIGN FOR APPROVAL:**

1. DISPLAY TYPE	■ TN □ HTN □ STN	5. DRIVE METHOD	1/4 DUTY 1/3 BIAS	NAME	DATE	REMARK: 'X.X' SYMBOLIZE ID NO.
DISPLAY SIZE	79*37*39	6. OPERATING VOLTAGE	3.0V	C/D DESIGN BY	WJY2015/10/28	
2. VIEWING DIRECTION	12 O' CLOCK	7. OPERATING TEMP	0°C~+50°C	CHECKED BY		LUMMAX ELECTRONICS CO., LTD
3. DISPLAY MODE	POSITIVE	8. STORAGE TEMP	-10°C~+60°C	APPROVED BY		
4. REAR POLARIZER	REFLECTIVE	9. CONNECTOR	□ ZEBRA □ HEAD	PAGE: 2/4	REV: D	TOLERANCE: ±0.2
				UNIT: mm	SCALE: NTS	DRAWING NO: GH0042-TRB
						CUSTOMER NO: 3747(1)
						PCS: 45